

SlowStop® Energy Absorbing Bollard – Type 2.5 (SS-T2.5Y-100)



www.a-csys-slowstop.be

Introduced to fit between our Type 2 and Type 3 models, the Type 2.5 is most efficient for heavy duty applications with limited speeds or vehicle masses. Protect against heavy fork lifts and slow moving medium lorries.

Color: RAL 1023 Yellow Bollard on RAL 9005 Black Base


Diameter: 139,7 mm (6,3 mm wall)

Height: 100 cm

Set Screws: 6 M16 x 2,00
8mm Hex

Cap: Black Plastic

Installs with six (6)
Concrete Anchor Screws



| MASS (KG) | 3000 | 4000 | 5000 | 6000 | 7000 | 8000 | 9000 | 10000 | 15000 | 20000 | 25000 |
|-------------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| SPEED (KPH) | | | | | | | | | | | |
| 3.0 | | | | | | | | | | | |
| 3.5 | | | | | | | | | | | |
| 4.0 | | | | | | | | | | | |
| 4.5 | | | | | | | | | | | |
| 5.0 | | | | | | | | | | | |
| 5.5 | | | | | | | | | | | |
| 6.0 | | | | | | | | | | | |
| 6.5 | | | | | | | | | | | |
| 7.0 | | | | | | | | | | | |
| 7.5 | | | | | | | | | | | |
| 8.0 | | | | | | | | | | | |
| 8.5 | | | | | | | | | | | |
| 9.0 | | | | | | | | | | | |
| 9.5 | | | | | | | | | | | |

No Damage / Negligible Damage
Will Stop / Potential Damage to Guard
Guard is under-sized

SPECIFICATIONS

- Stopping Power Rating: 14.000 joules | 90 kN
- Temperature Rating: -40° to 70°C
- Pipe Coating: EN-ISO 1461 Galvanized + Polyester Powder Coat
- Base Coating: Environmentally Friendly Water-Based KTL Coating + Polyester Powder Coat. C5I corrosion resistance.
- Frangible base eliminates floor damage. Safe for structural concrete.

RECOMMENDED USES



- Heavy Equipment Guarding
- Door and Wall Protection
- Parking Facilities
- Utility Protection
- Pedestrian Safety
- Access Denial
- Fuel Pump Protection
- Not for Hostile Vehicle Security



www.a-csys.be

Tél. : +32 (0) 4 338 00 04
E-mail : info@a-csys.be

Parc Industriel 16
4400 Flémalle (Liège) – Belgique